

Oberon Product Tech Sheet

ARC15™ – Arc Flash Suits for NFPA 70E Category 2* To Protect Electrical Workers from Arc Flash Heat Exposures

HEADLINES

- Material: 55% Inherently FR modacrylic and 45% cotton
- Fabric Arc Rating (ATPV): 24 cal/cm²
- Fabric Weight: 14 oz/yd²
- Hood Arc Rating (ATPV): 24 cal/cm²
- VLT: 60%

FEATURES

Oberon's ARC15 suit is inherently Flame Resistant (FR). It will remain Flame Resistant after years of frequent and repeated laundering. ARC15 is the lightest weight arc flash suit in the market at this protection level. The outer surface of the shield window is scratch resistant coated to last longer. The inner surface of the shield is antifog coated for clearer visibility.

APPLICATION

Every lineman, electrical contractor, industrial electrician and thermographer, working in the proximity of an energized circuit, is at risk of serious or even fatal burns. Every day in the USA, there are approximately 10 Arc Flash incidents and up to 3 fatalities. An Arc Flash can cause 3rd degree burns in a fraction of a second. NFPA 70E standard was developed to address this hazard, establishing a series of work practices and protective measures to reduce the risk of injury.

ORDERING

#IFR2STA: Coverall + Arc Flash Hood with Hard Cap
#IFR2STB: Coat and Bib-Overalls + Arc Flash Hood with Hard Cap
Color: Denim Blue
Size: S, M, L, XL, 2XL, 3XL, 4XL, 5XL

RELATED PRODUCTS

- Arc Flash DailyWear™ HRC1 & 2
 - Electrical Rubber Insulated Tools
 - Arc Flash Cooling Vest
 - FreshAir™ Hood Ventilation System
 - Spectacles for impact protection
 - Arc Suppression Blankets
- Arc Flash suits offered in kits containing clothing, hood, gloves, hearing protection, spectacles & storage bag

DESCRIPTION

Oberon's ARC15 suit is designed to provide protection from arc flash heat exposures. The suit exceeds the requirements of NFPA 70E Hazard Risk Category 2* (HRC2*), up to 24 cal/cm². Oberon's ARC15 suit is manufactured with 55% inherently FR modacrylic, and 45% cotton. This high technology lightweight and proprietary fabric can reduce heat stress.

The coats and coveralls feature Nomex® sleeve cuffs and double front closures with FR zipper tape and Dupont® Nomex® Velcro® safety flap.

The bib-overalls include FRT suspenders and an expandable pleat at the waist for adjustable fit and comfort.

The bib-overalls and the coveralls feature wide pant legs that are easy to slide on and off. There are no open pleats in the pant legs that could compromise safety if not properly closed.

The hood window is manufactured with Oberon's proprietary ArcX™ energy absorbing polycarbonate material and is coated to be scratch resistant outside and antifog inside.

Standards Compliance: ANSI Z87.1-2003, NFPA 70E-2004 & ASTM F1506-02a. Tested according to ASTM F1959-05a & ASTM F2178-02. NFPA 70E Article 130.7(C)(1) requires that an employee working within the Flash Protection Boundary wears protective clothing and other personal protective equipment.

Note: PPE should be chosen to meet or exceed the expected incident energy at the potential work site.



22 Logan Street, New Bedford, MA 02740-7324

Tel: 800-322-3348

Fax: 508-999-4443

www.oberoncompany.com

safety@oberoncompany.com